

CONNECTING POWER/CIRCUIT
SIZE REQUIREMENTS

Damage caused by connecting the amplifier to improper AC voltage is not covered by any warranty. Note: Always turn off and disconnect the amplifier from main voltage before making audio connections, and as an extra precaution, have the volume controls turned down during power-up.

SPECIFICATIONS

➤ 80 STEREO POWER (1KHZ):	> 100 W	➤ INTERMODULATION DISTORTION (AT 10% RATED POWER 1KHZ):	> <0.1%
➤ 40 STEREO POWER (1KHZ):	> 140 W	➤ CROSSTALK:	> -70 dB
➤ 80 BRIDGE POWER (1KHZ):	> 245 W	➤ FREQUENCY RESPONSE:	20 Hz-20 kHz +/-0.5 dB
➤ SLEW RATE (AT 1KHZ):	> 28 V/us	➤ INPUT IMPEDANCE:	(Balanced) 20 KΩ (Unbalanced) 10 KΩ
➤ INPUT SENSITIVITY (1KHZ):	> 0.775V (0 dBu)	➤ DAMPING FACTOR (100HZ, 8Ω):	250
➤ TOTAL HARMONIC DISTORTION (1KHZ):	> <0.1%	➤ SIGNAL TO NOISE RATIO (A WEIGHTED):	>103 dB
		➤ AMPLIFIER:	Class AB
		➤ DIMENSIONS:	483 W x 44 H x 386 D (mm) (19" x 1.75" x 15.2")
		➤ WEIGHT:	7.7kg (17 lb)

©2026 Avantone Pro. CLA-100, The Avantone Pro name and logo are trademarks or registered trademarks of Avantone Pro. This manual and any associated intellectual property are subject to copyright protection. No part of this document may be reproduced in any form without explicit written consent from Avantone Pro.

RAD Distribution
180 Carpenter Ave.
Middletown, NY 10940

Revised 08/28/26

COOLING REQUIREMENTS

The power amplifiers use a convection cooling system to maintain an even operating temperature. Air enters through the vents on each side and the bottom of the amplifier chassis and exits through the sides and top of the chassis. Make sure that there is enough space around the sides of the amp to allow the heated air to exit. If the amp is rack-mounted, do not use doors unless you have forced air cooling. Note: Whatever type of rack you are using, make sure that the heated air can escape freely, and that there is no resistance to the intake of cool air through the chassis.

CLA-100



IMPORTANT SAFETY INSTRUCTIONS

Exposure to extremely high noise levels may cause permanent hearing loss. Individuals vary considerably in susceptibility to noise-induced hearing loss, but nearly everyone will lose some hearing if exposed to sufficiently intense noise for a period of time. The U.S. Government's Occupational Safety and Health Administration (OSHA) have specified the permissible noise level exposures shown in the following chart.

According to OSHA, any exposure in excess of these permissible limits could result in some hearing loss. To ensure against potentially dangerous exposure to high sound pressure levels, it is recommended that all persons exposed to equipment capable of producing high sound pressure levels use hearing protectors while the equipment is in operation. Ear plugs or protectors in the ear canals or over the ears must be worn when operating the equipment in order to prevent permanent hearing loss if exposure is in excess of the limits set forth here.

Duration, per day in hours	Sound Level dBA, slow response	Typical example
8	90	Duo in small club
6	92	
4	95	Subway train
3	97	
2	100	Very loud classical music
1.5	102	
1	105	That couple screaming at each other
0.5	110	
<0.25	115	Loudest parts at a rock concert



The CLA-100 complies with all applicable RoHS / WEEE European Union directives. This product complies with IEC62386.

Do not attempt to service this unit yourself, as it will void your warranty. Please check your unit carefully upon receipt and return to place of purchase immediately if there are any problems with the product. After that, the standard AVANTONE 5 YEAR warranty will apply to defects in materials and workmanship.

U.S.A.

Should your Avantone product require service, please contact the Avantone Pro Service Department via the Contact page on AvantonePro.com. **You must obtain an RA # (Return Authorization number) from us before shipping a unit back to us. This RA # must be clearly written on the outside of the box.**

Please safely pack the units. It is best to use the original packing materials. AVANTONE PRO cannot be responsible for any damages incurred in shipping to us due to poor packaging. PLEASE PACK CAREFULLY and FULLY INSURE THE SHIPMENT.

INTERNATIONAL

For service or warranty assistance, please contact the AVANTONE PRO distributor in your country through the dealer from whom you purchased this product.

LIMITED 5 YEAR WARRANTY

AVANTONE CLA-100s are warranted by Avantone Pro to be free from defects in materials and workmanship for the period of 5 YEARS to the original purchaser. In the event of such defects, the Avantone Pro product will be repaired without charge or, at our option, replaced with a new one if delivered to Avantone Pro prepaid, together with a copy of the sales slip or other proof of purchase date. The warranty excludes problems due to normal wear, abuse, shipping damage or failure to use the product in accordance with the specifications.

All speaker systems are vulnerable to damage from sustained amplifier clipping. This can be described as a distortion of the signal caused by the amplifier running out of headroom. Heat will then be generated in the voice coil of the driver beyond the heat handling capabilities of wire and glue. At some point the voice coil will burn, causing the speaker to sound very distorted; eventually the driver will stop working.

All parts and labor are covered under this Limited Warranty. However, if it is determined by AVANTONE PRO that the voice coil was burned due to sustained amplifier clipping, we reserve the right to charge the customer for the cost of the repair, since this is considered abuse.

Avantone Pro shall not be liable for damages based upon inconvenience, loss of use of the product, loss of time, interrupted operation or commercial loss or any other damages, whether incidental, consequential, or otherwise. This warranty gives you specific legal rights, and you may have other rights, which will vary from state to state.

This warranty is not transferable.

The CLA-100 Studio Reference Amplifier is designed to be used in a studio environment requiring high power output with no fan noise. Under testing, it delivers a powerful 100 watts into 8 ohms and can run at one third power without thermal fault.

The CLA-100 was designed to be paired with large format studio monitors, but it can be used with just about any demanding speaker load. Very low distortion, steady performance under harsh conditions, and an open and transparent sound make this an obvious choice for discerning studios.

QUICK START GUIDE

- > Select the operating voltage. If you are changing voltages, please be sure to change fuse values as specified on the rear panel
- > Place volume controls to minimum
- > Turn on all upstream equipment; run outputs at minimum
- > Select operating mode. Choose from Stereo or Bridged Mono modes.
- > Connect audio input, speaker cables and power cord with power switch in OFF position
- > Turn on power switch
- > Plug power into AC source
- > Adjust volume to appropriate level at source and speaker

CONNECTING YOUR CLA-100

Before plugging in and powering up your CLA-100 please take a moment to be certain that the proper AC MAINS operating voltage setting has been selected on the rear panel.

THERMAL PROTECTION

If the heat sink temperature reaches an abnormally high temperature, the amplifier will protect itself by disconnecting loudspeakers and shutting down until sufficiently cooled.

DC VOLTAGE PROTECTION

If an amplifier channel detects DC voltage at its output terminals, the output relay will immediately open to prevent loudspeaker damage.

REAR PANEL CONNECTIONS

1. BALANCED INPUT: The XLR inputs accept a BALANCED male XLR plug as well as a 3-conductor BALANCED TRS 1/4" or a 2 conductor UNBALANCED TS 1/4" male plug. For unbalanced operation with a TS connector the minus signal is automatically grounded.

2. LINK OUTPUT: This XLR output sends a balanced, line-level copy of the input signal. Useful if you're running a second pair of active monitors; an active subwoofer, or an additional monitor amplifier.

3. VOLTAGE SELECT and AC MAINS INPUT: There is a switch on the rear panel for selecting the proper AC/MAINS operating voltage for your location. Please be sure to use the correct specified fuse value for your location. Fuse tray is incorporated into the IEC320 receptacle on the rear panel.

4. SPEAKER OUTPUTS: Binding posts are provided. In mono/bridge operation mode, the two positive terminals are driven anti-phase. DO NOT GROUND any of the speaker terminals in bridge mode.

INSTALLATION AND MOUNTING

The CLA-100 is a 1U amplifier that can be mounted in a standard 19-inch rack. Four front panel mounting holes are provided.

SHORT CIRCUIT

If an output is shorted (i.e., defective speakers or crossed speaker wires) the ZSP and thermal protection circuits will automatically protect the amplifier. The ZSP circuit senses the short circuit as an extremely stressful load condition and attenuates the signal, protecting the channel's output transistors from over current stress. If the short circuit remains, the load will be disconnected by the thermal protection circuit.

STEREO: both channels driven separately

BRIDGED MONO: both channels operate together as a single amplifier. Channel A is the input, and Channel A output is in phase, channel B output is out of phase.

